

Hose clamps



The Ezyklik hose clamp

Specially designed for hose clamping applications where space is restricted, the new Ezyklik (patent pending) hose clamp offers the convenience of the Herbie Clip with a narrower head.

The unique design of the Ezyklik ensures strong, reliable clamping with the added security of a special interlocking head to ensure that the Ezyklik maintains clamping integrity in the most arduous applications.

Manufactured from Nylon 6.6,* the Ezyklik has the following characteristics:

- No moving parts - will not seize
- Low profile head will fit into small spaces
- Full installation tooling support
- Choice of installation - pre-fit onto hose or wrap around once the hose is in place
- Can be quickly released using pliers
- Lightweight and easy to use
- No sharp edges to cut the operator
- Strong UV resistance
- Temperature range -40°C to +150°C
- Seals hosework up to 8 bar (depending on hose and fitting)
- UL listed
- ROHS compliant

Because of the non-existent dynamic range of the Ezyklik, each size is made on a case by case basis. If you feel you have an application that would be ideally suited for this product please send us a sample of the hose and spigot that you are using. We will then design free of charge** an Ezyklik to fit your application. The sizes shown in the table opposite are already in production and we expect many more to be added in the short term.

*The Ezyklik will be available on request in Polypropylene.





** Dependant on estimated annual volume.

Installation and removal



Ezyklik manual and pneumatic installation tools.

Ezyklik is easy to install and remove using a choice of manual or semi-automatic pneumatic tools.



NEW

Ezy Klik™ sizes

Closed diameter (A)		Width (B)	
mm	inch	mm	inch
8.5	0.33	8.0	0.31
9.5	0.37	8.0	0.31
11.4	0.45	8.0	0.31
12.0	0.47	8.0	0.31
12.5	0.49	8.0	0.31
14.5	0.57	8.0	0.31
15.0	0.59	8.0	0.31
15.7	0.62	8.0	0.31
15.9	0.62	8.0	0.31
16.5	0.65	8.0	0.31
16.8	0.66	8.0	0.31
17.1	0.67	8.0	0.31
17.5	0.69	8.0	0.31
20.8	0.82	8.0	0.31
22.0	0.86	8.0	0.31
24.7	0.97	8.0	0.31
25.8	1.01	8.0	0.31
26.8	1.05	8.0	0.31
28.0	1.10	8.0	0.31
30.6	1.20	9.0	0.35
31.4	1.23	9.0	0.35
36.5	1.43	9.0	0.35
42.4	1.67	9.0	0.35
43.3	1.70	9.0	0.35
45.5	1.79	9.0	0.35



These photographs illustrate how the unique design of the Ezyklik allows for secure and reliable hose clamping in restricted spaces.



UK Sales HCL Fasteners Limited, First Avenue, Westfield Industrial Estate, Radstock, Bath BA3 4BS, UK
 Tel: +44 (0)1761 417714 Fax: +44 (0)1761 417710 Email: sales@hclfasteners.co.uk www.hclfasteners.co.uk
North American Sales HCL Fasteners NA, 6 Erolid Court, Allendale, New Jersey, 07401, USA
 Tel: 201 962 8214 Fax: 201 825 4880 Email: sales@hclfasteners.com www.hclfasteners.com



ISO 9001:2000